



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 17/30	A1	(11) International Publication Number: WO 97/17662
		(43) International Publication Date: 15 May 1997 (15.05.97)

(21) International Application Number: PCT/US96/17687

(22) International Filing Date: 6 November 1996 (06.11.96)

(30) Priority Data:
08/554,168 6 November 1995 (06.11.95) US

(71) Applicant: C/NET, INC. [US/US]; 150 Chestnut Street, San Francisco, CA 94111 (US).


(72) Inventors: ROSENBERG, Jonathan; 18 Wellington Drive, Annandale, NJ 08801 (US). GANDHI, Munish; 611 West Porter Way, Bridgewater, NJ 08807 (US).

(74) Agents: GALLIANI, William, S. et al.; Flehr, Hohbach, Test, Albritton & Herbert, Suite 3400, 4 Embarcadero Center, San Francisco, CA 94111-4187 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: METHOD AND APPARATUS FOR SERVER-INDEPENDENT CACHING OF DYNAMICALLY-GENERATED CUSTOMIZED PAGES



(57) Abstract

The invention is a method and apparatus for operating a client-server computer network (20) such that a server computer (24) dynamically generates and then stores customized pages requested from a client computer (22). Subsequent requests for previously generated customized pages are retrieved from cache (50) in the server computer. Since previously generated customized pages need not be re-generated, computational overhead is reduced. This functionality is achieved by transforming a file request into a customized file request (84). The customized file request includes the original file request and a selected attribute of a computer user, such as browser name, computer domain, or computer platform. When a customized file request cannot be matched to an existing file on the computer server, an error indication is generated (86). A customized page corresponding to the file request is created in response to the error indication (88).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

METHOD AND APPARATUS FOR SERVER-INDEPENDENT CACHING OF DYNAMICALLY-GENERATED CUSTOMIZED PAGES

Brief Description of the Invention

This invention relates generally to the operation of client-server computer networks. More particularly, this invention relates to a general technique for using a server computer to store a dynamically-generated customized page so that
5 subsequent requests for the same customized page can be retrieved from storage without having to dynamically re-generate the customized page.

Background of the Invention

The World Wide Web (WWW) of computers is a large collection of
10 computers operated under a client-server computer network model. In a client-server computer network, a client computer requests information from a server computer. In response to the request, the server computer passes the requested information to the client computer. Server computers are typically operated by large information providers, such as commercial organizations, governmental units,
15 and universities. Client computers are typically operated by individuals.

To insure interoperability in a client-server computer network, various protocols are observed. For example, a protocol known as the Hypertext Transport Protocol (HTTP) is used to move hypertext files across the WWW. In addition, the WWW observes a protocol for organizing and presenting information
20 known as the Hypertext Markup Language (HTML) protocol.

The HTTP protocol supports a feature known as "dynamically-generated customized pages". A dynamically-generated customized page results in a set of

information in a particular format. The same set of information can be presented in a number of ways, depending upon whether a particular format is supported by a client computer. For example, a first client computer may support the ability to represent information in a number of columns, while a second client computer may support the ability to represent information in a table. Thus, a server computer receiving a request from the first client computer will dynamically generate the requested information in a format with columns. It will respond to a request from the second client computer by dynamically generating the requested information in table format. In this example, two customized pages are created to represent the same information.

Computer programs are used to dynamically-generate customized pages. Existing computer programs to generate customized pages do not scale well for large numbers of requests. In other words, existing methods provide a relatively slow response when a large number of requests are made for customized pages. This slow response time is attributable to the fact that in existing systems, a computer program must be executed to dynamically-generate a customized page for each request.

In view of the foregoing, it would be highly desirable to provide a technique to efficiently respond to a large number of requests for customized pages.

Summary of the Invention

The invention is a method and apparatus for operating a client-server computer network such that a server computer dynamically generates and then stores customized pages requested from a client computer. Subsequent requests for previously generated customized pages are retrieved from a cache in the server computer. Since previously generated customized pages need not be re-generated, computational overhead is reduced. This functionality is achieved by transforming a file request into a customized file request. The customized file request includes the original file request and at least one selected attribute of a computer user, such as browser name, computer domain, or computer platform. When a customized file request cannot be matched to an existing file on the computer server, an error

indication is generated. A customized page corresponding to the file request is created in response to the error indication.

The invention is highly advantageous because it does not require the dynamic-generation of a customized page every time a customized page is requested.

- 5 Instead, previously generated customized pages can be returned to a client computer without incurring the computational overhead of re-generating the same customized page. This functionality is achieved in a server-independent manner. That is, this functionality is invoked in response to a file search error that all HTTP server programs utilize. Advantageously, the invention exploits inherent
- 10 features in existing HTTP server programs. Thus, implementation of the invention does not require a customized server program and can otherwise be readily operated with existing server programs.

Brief Description of the Drawings

- 15 For a better understanding of the nature and objects of the invention, reference should be made to the following detailed description taken in conjunction with the accompanying drawings, in which:

FIGURE 1 illustrates a client-server computer network that may be operated in accordance with the present invention.

- 20 FIGURE 2 illustrates the processing associated with one embodiment of the present invention.

FIGURE 3 illustrates the processing performed by various software programs in one embodiment of the invention.

- FIGURE 4 illustrates the processing performed by various software programs
- 25 in one embodiment of the invention.

FIGURE 5 is a more detailed representation of various file handling operations performed in accordance with the invention.

Like reference numerals refer to corresponding parts throughout the several views of the drawings.

Detailed Description of the Invention

Figure 1 illustrates a client-server computer network 20 that may be operated in accordance with the present invention. The network 20 includes at least one client computer 22 and at least one server computer 24. The client computer 22
5 and the server computer 24 are connected by a transmission channel 26, which may be any wire or wireless transmission channel.

The client computer 22 is a standard computer including a Central Processing Unit (CPU) 30 connected to a memory (primary and/or secondary) 32. The memory 32 stores a number of computer programs, including a "browser" 34. As
10 known in the art, a browser is used to communicate with remote server computers 24 and to visually present the information received from such computers. The client computer 22 establishes network communications through a standard network connection device 36.

The server computer 24 includes standard server computer components,
15 including a network connection device 40, a CPU 42, and a memory (primary and/or secondary) 44. The memory 44 stores a set of computer programs to implement the processing associated with the invention. The memory 44 stores a standard communication program 46 to realize standard network communications. The memory 44 also stores a standard server program 48. The program 48 may
20 be a standard HTTP software server program, such as: NETSITE™, from Netscape, Inc., Mountain View, California; NCSA from the National Center for Supercomputing Applications, Champaign, Illinois; or APACHE™, from Apache HTTP Server Project, Lincoln, Nebraska.

In accordance with the invention, the standard software server program 48 is
25 instructed to make a call to a novel front door program 49. Standard HTTP server programs include a feature that allows another program to be called when a certain condition is satisfied. In this case, the front door program 49 is called by the server program 48 when the server program 48 receives a request for a standard file name, instead of a request for a customized file name. When invoked by the
30 server program 48, the front door program 49 transforms the standard file name into a customized file request. The customized file request is typically implemented as a combination of the initial standard file name and a selected

attribute of a computer user. The selected attribute may be the browser used by the client computer 22, the domain name of the user's network connection, the platform (computer type) of the client computer 22, or some other attribute that specifies the format capabilities of the client computer 22.

- 5 The memory 44 also stores a caching page generator program 50. This program is invoked when a customized file request cannot be matched to an existing set of files stored on the server computer 24. In this case, conventional computer servers generate an error indication that is passed back to the client computer. In the HTTP protocol, this error indication is Error 404. The caching
10 page generator program 50 of the invention intercepts any error indication by creating a customized file corresponding to the customized file request. Thus, the present invention uses an inherent feature of conventional HTTP servers, namely the file location error signal, to invoke the caching page generator program 50. Instead of simply returning an error signal to a client computer 24, the caching
15 page generator program 50 generates a customized file for the client computer 24.

The customized file created by the server computer 24 is stored by the file handler program 52. The server program 48 simultaneously passes the contents of the customized file to the client computer 24.

- This brief description of the invention is more clearly understood in reference
20 to Figure 2. Figure 2 illustrates processing steps that may be executed in accordance with one embodiment of the invention. The first processing step shown in Figure 2 is to establish a "state connection" with a server computer 24 (step 60). The HTTP protocol used by the WWW is "stateless". That is, each request to a server computer 24 from a client computer 22 operates by: (1) establishing a
25 connection between a client computer 22 and a server computer 24; (2) sending a request from the client computer 22 to the server computer 24; (3) returning the requested information from the server computer 24 to the client computer 22; and (4) closing the connection between the client computer 22 and the server computer 24. Since each interaction between a client computer 22 and a server computer 24
30 results in the opening and closing of a communication session, the server computer 24 does not maintain "state information" regarding previous connections to a particular client computer 24.

In accordance with the invention, a customized file name is created when an initial connection is made between a client computer 22 and a server computer 24. Thus, in a subsequent connection between the client computer 22 and the server computer 24, the customized file name is effectively attributed to a previous state
5 connection with a particular client computer 22. Once this state connection is established, the customized file name is processed in accordance with the invention, as will be described below.

The customized file name may be implemented as a CURL. CURL is an acronym for Customized Uniform Resource Locator. A Uniform Resource Locator
10 or URL specifies a protocol, a computer, and a file. A typical URL is "http://cnet/123". This URL is an instruction to retrieve the file 123 from the computer "cnet" using the HTTP protocol. A URL may also be used to invoke a specified function on a remote computer, with the remote computer returning the results of the invoked and executed function.

15 As shown in Figure 2, the customized file request or CURL is used to find a match (step 62). That is, the CURL is compared to the file names stored on the server computer 24. If a match is found, then a customized page is sent from the server computer 24 to the client computer 22 (step 64). If no match is found, then an error indication is generated on the server computer 24. The caching page
20 generator program 50 responds to the error indication by creating a customized page (step 66). A customized page is created by using information in the customized file request. As indicated above, the customized file request is typically implemented as a combination of the initial file name and a selected attribute of a computer user. The server computer 24 uses the initial file name to
25 identify the set of information that will be sent to the client computer 22. It uses the selected attribute to customize the set of information. As will be discussed below, the selected attribute provides sufficient information for the server computer 24 to identify what formats are supported by the client computer 22.

After the creation of the customized page (step 66), the list of file names is
30 updated (step 68). The customized page is then stored (step 70) and returned (step 72) to the client computer 22 (steps 68, 70, and 72 may be performed simultaneously).

At this point, a number of unique attributes of the present invention will be recognizable to those skilled in the art. A primary novel attribute of the present invention is that it is capable of storing and retrieving customized files and the customized pages contained therein. Thus, a program need not be executed to
5 form a customized file each time a customized file is called. Instead, the program is only executed once. Thereafter, the customized file is stored in the memory 44 of the server computer 24. Consequently, subsequent requests for the customized file can be quickly processed.

This highly desirable functionality is achieved through the specification of a
10 customized file name format. The customized file name format is immediately invoked with an original file request at a computer server 24.

The present invention is highly advantageous because it can be implemented with any number of HTTP software server programs. Thus, it is considered server-independent. The invention is also advantageous in its ability to use
15 standard server computer 24 resources, such as the native file handling capabilities of a server computer 24. The details of the invention and its benefits will be more fully appreciated with reference to Figures 3-5.

Figure 3 illustrates the processing performed by various software modules of the present invention. As shown in the figure, a browser 32 is used to request a
20 front door connection at a server computer 24 (step 80). The connection request is then processed by the server program 48 by calling the front door program 49 (step 82). The front door program 49 processes the request by forming a CURL (step 83). For example, suppose that the connection request indicated that "pageX" on the server computer 24 should be returned to the client computer 22.
25 Further, suppose that the client computer 22 is using "browserY" (through its interaction with the client computer 22, the server computer 24 knows which browser 34 the client computer 22 is using). In this case, the customized file may be defined as "pageX, browserY". In this example, the customized file name is a combination of a requested page and a selected attribute, namely the browser type.
30 The customized file name may be formed in any number of ways. The only limitations in this regard are that the requested page must be recognizable, the

selected attribute must be recognizable, and the name must be a valid name for the controlling operating system.

Note that in the prior art, the request for "pageX" would have simply resulted in the return of the "pageX" information to the client computer 22. In contrast,
5 the present invention changes the name of the initial file request, and then "redirects" it back to the server computer 24. As known in the art a "redirect" command is an address passed from a server computer 24 to a client computer 24, which the client computer 24 uses to access a server computer specified in the address. For example, the CURL generation operation of step 83 may result in the
10 following redirect command being generated "http://server_24/pageX,browserY". The browser 24 receives this command and executes it (step 84), resulting in a re-connection to the server 24 ("server_24") that generated the CURL.

At this point, the server program 48 recognizes the customized file format observed by the incoming command. Namely, it notes that a page is specified
15 ("pageX") and a selected attribute is specified ("browserY"). Consequently, the server computer 24 recognizes that a previous connection has been made with this client computer 22 and there is no need to generate a customized file name. Instead, the program 48 attempts to match the customized file name (CURL) to a list of files stored on the server computer 24 (step 86). In an initial state, an error
20 indication will be generated. That is, when the server computer 24 first comes on line, it has not generated any customized pages. Thus, when an initial file request comes in and it is transformed into a customized file request, an attempt to match the customized file request will fail, thereby producing an error indication.

As indicated above, the caching page generator 50 responds to an error
25 indication by creating a customized page (step 88). Figure 3 refers to the creation of a custom front page. Typically, on an initial connection, a client computer 22 wants to observe the front page of a web site.

The customized page is generated by relying upon the information in the customized file request. The page specified in the initial file request is used to
30 identify the set of information that will be returned to the client computer 24. The selected attribute of the customized file request will specify the format of the returned information. For example, "PageX" is a set of information that can be

represented in a number of formats, say in a column or in a table form. The format in which it is returned to the client computer 22 depends upon a selected attribute of the client computer 22 requesting the information. As indicated above, the selected attribute may be the browser 34 of the client computer 22. In accordance with the invention, standard features of different browsers are stored by the server computer 24. Therefore, when a particular browser 34 is identified by the server computer 24, the server computer 24 can elect a particular format in which to return the requested information. Expanding on this example, assume that "BrowserY" supports tables, but not columns. When the server computer 24 receives the request for "pageX", it notes that "BrowserY" supports tables, and therefore, if appropriate, presents the information of "pageX" in a table format, thus creating a customized page.

As shown in Figure 3, the customized page is then stored (step 90) by the file handler 52. In addition, it is passed to the browser (step 92). The customized page passed to the browser 34 may include a set of customized file requests embedded therein. For example, when a front page of a web site is returned to a browser 34, it is likely that the client computer 22 will select a link in the customized front page that request additional information from the same server computer 24 to which it is presently connected. Thus, the caching page generator 50 of the invention may change each link in a customized page to include a customized file request. For example, suppose that an un-customized front page includes a link to "pageA" of the originally accessed server computer 24. The caching page generator 50 may change this link to read "pageA, BrowserY". That is, the original page specification is appended with the previously identified selected attribute.

If the caching page generator 50 has modified the links in a customized page returned to the browser 34, then activating the link will allow the server program 48 to identify the customized file name format. Consequently, it will attempt to match the customized file name to the list of existing file names. If the caching page generator 50 has not inserted customized file names into a customized page, then the original page specification will be used. This will result in the generation of a CURL (steps 82, 83).

In the present example, an assumption is made that the caching page generator 50 created a customized page with customized file names. This results in the server program 48 attempting to match the activated customized file name with a file name existing on the server computer 24. If the specified customized page does not exist, it is generated in the manner previously described (step 96). Thereafter, the generated customized page is stored by the file handler 52 (step 98) and is passed to the browser 34, where it is displayed (step 100).

The processing shown in Figure 4 generally corresponds to the processing shown in Figure 3, with one notable exception. In Figure 4, the caching page generator 50 is not invoked because the requested customized pages were previously generated, and therefore they exist in the server memory 46.

Note at step 110 in Figure 4 that the attempt to match the CURL results in a file hit, meaning that the requested file was generated from a previous transaction and resides in memory. A fetch command is then processed by the file handler 52, which returns the requested file. The same operation is then repeated at steps 118 and 120.

Figure 5 is a more detailed illustration of the file handling operations associated with the present invention. Note that an initial file request is handled by the front door program 49. As previously discussed, this results in the redirection of a customized file request back to the server computer 24. At this point the server program 48 attempts to match the incoming customized file request with its list of existing files 136. Figure 5 illustrates three standard files, File X, File Y, and File Z. Each file is listed in the list of files 136. Each listed file has an associated pointer, as shown in Figure 5, to the server computer 24 memory 44 location that holds its corresponding file content.

The list of files 136 of Figure 5 also includes a reference to a customized file "Y,C". The customized file "Y,C" has a pointer to a memory location that holds the contents of a previously created customized page.

Suppose, the incoming customized file name is "Z,C". In this case, when the server program 48 attempts to match the file name with the list of file names, it results in an error indication. The error indication is identified by a customized page generator 146 of the caching page generator 50. The customized page

generator 146 uses the original page designation to identify File Z in memory and it uses the selected attribute to determine how the information in File Z should be returned to the client computer 22. This information is then used to create Custom File Z 150. The file handler 52 stores Custom File Z 150. In addition, Custom
5 File Z is passed to the server program 48. After creating a customized page, the customized page generator 146 updates the list of files 136. Thus, in this example, the list of files 136 would be amended to include file name "Z,C".

The foregoing descriptions of specific embodiments of the present invention are presented for purposes of illustration and description. They are not intended to
10 be exhaustive or to limit the invention to the precise forms disclosed, obviously many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various
15 modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the following Claims and their equivalents.

IN THE CLAIMS:

1. A method of operating a server computer, said method comprising the steps of:
 - 5 storing a set of standard files and customized files on said server computer;
generating an error indication when a requested file name cannot be matched to said standard files and said customized files; and
creating a customized page corresponding to said requested file name in response to said error indication.
- 10 2. The method of claim 1 wherein said requested file name is a customized file name specified in a customized page generated by said server computer.
3. The method of claim 1 further comprising the step of producing said requested
15 file name from an initial file request.
4. The method of claim 3 wherein said producing step includes the step of combining said initial file request with a selected attribute of a computer user to produce said requested file name.
- 20 5. The method of claim 4 wherein said combining step includes the step of using a selected attribute from the group including browser name, computer domain, and computer platform.
- 25 6. The method of claim 3 wherein said selected attribute is used in said creating step to create said customized page.
7. The method of claim 1 further comprising the step of updating a list of file names in response to said creating step.
- 30 8. The method of claim 1 wherein said error indication of said generating step is a Hypertext Transport Protocol (HTTP) path error.

9. A method of operating a server computer, said method comprising the steps of:
- transforming an initial file request into a customized file request;
 - generating an error indication when said customized file request cannot be
 - 5 matched to an existing file stored on said server computer; and
 - creating a customized page corresponding to said customized file request in response to said error indication.
10. The method of claim 9 wherein said transforming step includes the step of
- 10 combining said initial file request with a selected attribute of a computer user to produce said customized file request.
11. The method of claim 10 wherein said combining step includes the step of using a selected attribute from the group including browser name, computer
- 15 domain, and computer platform.
12. The method of claim 10 wherein said selected attribute is used in said creating step to create said customized page.
- 20 13. The method of claim 9 further comprising the step of updating a list of file names in response to said creating step.
14. The method of claim 9 wherein said error indication of said generating step is a Hypertext Transport Protocol (HTTP) path error.
- 25 15. A computer readable memory that can direct a computer to function in a specified manner, comprising:
- standard files and customized files stored in said computer memory; and
 - executable instructions stored in said memory, said executable instructions
 - 30 including:
- (A) instructions to generate an error indication when a requested file name cannot be matched to said standard files and said customized files;

(B) instructions to create a customized page corresponding to said requested file name in response to said error indication.

16. The computer readable memory of claim 15 further comprising (C)
5 instructions to produce said requested file name from an initial file request.

17. The computer readable memory of claim 16 wherein said instructions of element (C) include instructions to combine an initial file request with a selected attribute of a computer user to produce said requested file name.

10

18. The computer readable memory of claim 17 wherein said instructions of element (C) rely upon a default attribute as said selected attribute.

19. The computer readable memory of claim 17 further comprising (D)
15 instructions to use said selected attribute to create said customized page.

20. The computer readable memory of claim 15 further comprising (E) instructions to update a list of file names in response to the instructions of element (B).




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/17687

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :G06F 17/30
US CL :395/601, 619

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 395/601, 602, 606, 616, 619

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PROQUEST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US, A, 5,473,772 (HALLIWELL ET AL.) 05 December 1995, COL. 4-8.	1-4, 7, 9-10, 13, 15-17, & 20 ----- 5, 6, 8, 11-12, 14, & 18-19
Y	IEEE & COMPUTER MAGAZINE, SEPTEMBER 1993, OBRACZKA ET AL., "INTERNET RESOURCE DISCOVERY SERVICES", PAGES 13-18.	5, 6, 8, 11-12, 14, & 18-19

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later documents published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be part of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"A" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 22 JANUARY 1997	Date of mailing of the international search report 11 MAR 1997
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	Authorized officer THOMAS G BLACK Jr
Facsimile No. (703) 305-3230	Telephone No. (703) 305-9707